SET LAUFEN PRO N

Floorstanding WC combination with cistern with fixing holes for floor fixation 82795.4





TECHNICAL DATA


Order no.	82795.4
Certified to	EN 997
Specification	Washdown for 4,5/3-I-flush, Charge 737
	2 fixing holes
	with cistern flushing mechanism, water
	condensation insulation,
	Dual-Flush (4,5/3-I-flush), water inlet bottom
	right 1/2" brass
Outlet	vertical
Weight	29,7 kg
Accessories excl.	Seat and cover, order no. 89095.0
	Seat and cover with automatic lowering system,
	order no. 89095.1
Mounting acc. incl.	Fastening kit, order no. 89175.7
Colours	see colour table

SPECIFICATION TEXT Floorstanding WC pan washdown LAUFEN PRO N, sanitary ceramic, with cistern Dual-Flush (4,5/3-I-flush) EN 997, 4,5/3-I-flush, dimensions 360 x 650 x 890 mm outlet vertical 70 mm concealed fixation, 2 fixing holes Special feature: concealed surfaces directing water are fully glazed throughout, open water rim, vacuum checked Further options / accessories: Surface refinement LCC, WC seat and cover, &9095.0, WC seat and cover with automatic lowering &9095.1 Order no. &2795.4

TECHNICAL DRAWINGS / S 1 : 20







L众UFEN